

# Product Data Sheet

## NSB 170 BLUE



Specifically designed  
for unstable mains  
applications

- Ideal for demanding environments with unstable AC power
- High modulus polyphenylene plastic materials designed to withstand extended elevated operating temperatures and maintain high battery compression essential for reliable operation
- Modified electrochemistry for repeated outages
  - Optimized paste additives and grid alloy
  - Less reliance on full recharge following an outage
  - No need for regular overcharge factor
  - Capable of uncontrolled Partial State of Charge (uPSOC)\* operation without running down in capacity

\* For a detailed description of uPSOC, please see the Blue Star Technology Application Manual



# Product Data Sheet

## NSB 170 BLUE



### Technical Specifications

20 hour capacity to 1.75 Volts/Cell @ 27 °C	150 Ah
10 hour capacity to 1.80 Volts/Cell @ 25 °C	141 Ah
10 hour capacity to 1.80 Volts/Cell @ 20 °C	139 Ah
Float Voltage	2.27 +/- 0.02 Volts/Cell @ 25 °C
Nominal Voltage	12 V
Impedance (1kHz)	2.4 mΩ @ 25 °C (77 °F)
Conductance	2100 S
Short Circuit Current	6,000 A
Maximum Charge Current	no limit
Container Material	Modified PPO (UL 94 V-0)
Operating Temperature Range	-40°C (-40°F) to 65°C (149°F)

### Measurements

Height	320 mm (12.6 in)
Width	125 mm (4.9 in)
Depth	560 mm (22.0 in)
Weight	56 kg (123 lbs)
Terminal	Female M8 leak proof
Terminal Torque	8.0 Nm (71 in-lbs)

