

PMP 450 Subscriber Module

VERTICAL MARKETS AND SOLUTIONS

WIRELESS SERVICE PROVIDERS (WISPs)

- Rural connectivity
- Municipal connectivity
- Remote office connectivity
- Primary or redundant connectivity

GOVERNMENT PUBLIC SAFETY SECTOR

- Data Connectivity and Video Surveillance for Public Safety
- Disaster Recovery for Public Service
- Data Network for Public Works

ENTERPRISES

- Video surveillance backhaul
- Device/site monitoring
- LAN extension
- Leased line replacement



PMP 450 Subscriber Module

Introduction

The Cambium Networks PMP 450 is our industry-leading wireless access network platform. Our solution is ideal for industry verticals such as WISPs (Wireless Service Providers), Enterprises and the Government Public Safety Sector. Designed for fixed outdoor applications, the PMP 450 platform is optimized for rate, reach, reliability and throughput. It features the most resilient and effective set of wireless broadband technologies in the marketplace.

Now available in most popular global bands, 2.4, 3.5, 3.65 and 5 GHz, the Cambium Networks Point-to-Multipoint (PMP) 450 Subscriber Module (SM) supports tiered service models. Software defined upgrades allow throughput from 4 Mbps to 55 Mbps and as a result improve revenue optimization.

From the innovative GPS Synchronization options to interoperability with existing portfolio modules, the PMP 450 provides flexible deployment options that make it an excellent fit for high capacity, high reliability networks.

Main Differentiators

» **MAXIMIZED SPECTRAL EFFICIENCY IN DENSE SERVICES AREAS** is enabled by our innovative GPS Sync Technology in combination with long range and high density coverage. This allows for configuration of more subscribers utilizing fewer access points, while preserving quality of service in spectrum-constrained environments. By lowering installation costs and maintenance, GPS Sync reduces operating expenses and improves growth and profitability.

» **OPTIMAL TRIPLE PLAY BACKHAUL** empowered by effective Quality of Service (QoS) management allows providers to confidently offer triple play services – VoIP (Voice over IP), video and data. Providing customers with excellent service ensures their continued loyalty and transforms them into advocates, helping WISPs and enterprises expand their business.

» **CARRIER-GRADE RELIABLE HARDWARE** by Cambium Networks is constructed from high quality industrial components; it is outdoor-rated and rigorously tested to satisfy the most difficult environmental conditions. With 40-year MTBF, our equipment standards are unsurpassed in industries requiring fixed wireless broadband.

Powerful Features

The Cambium Networks PMP 450 platform is designed for growth. It allows service providers to efficiently and cost-effectively offer popular multi-media services that maximize their revenue - high-speed data and cloud access, video on demand, reliable fixed voice and VoIP. The PMP 450 solution provides reliable coverage across large service areas in urban, suburban, rural and remote locations.

2x2 MIMO-OFDM technology allows dual stream operation for most channel conditions, guaranteeing successful deployment of wireless networks in challenging environments.

Low latency of 3 - 5 ms effectively supports video and VoIP services. **Flexible channel width** (5, 10 and 20 MHz) allows users to select the most effective channel width for the current network environment. **256-QAM** modulation rate offers the unique ability to use the PMP 450 platform for services requiring fast and reliable transmission. **System performance** is ensured by vigorous testing with a compatible set of radios, guaranteeing predictable link budget results. Cambium Networks specifications are consistent with real life conditions.

PRODUCT														
MODEL NUMBERS (-005A THROUGH -008A ARE CONNECTORIZED)		4 Mbps			10 Mbps			20 Mbps			UNCAPPED			
	5 GHz	C054045C001A C054045C005A			C054045C002A C054045C006A			C054045C003A C054045C007A			C054045C004A C054045C008A			
	2.4 GHz	C024045C001A C024045C005A			C024045C002A C024045C006A			C024045C003A C024045C007A			C024045C004A C024045C008A			
	3.3-3.6 GHz	C035045C001A C035045C005A			C035045C002A C035045C006A			C035045C003A C035045C007A			C035045C004A C035045C008A			
	3.55-3.8 GHz*	C036045C001A C036045C005A			C036045C002A C036045C006A			C036045C003A C036045C007A			C036045C004A C036045C008A			
SPECTRUM														
CHANNEL SPACING	CONFIGURABLE ON 2.5 MHz INCREMENTS, SELECTABLE TO 50 KHz AT 3 GHz FREQUENCY													
FREQUENCY RANGE	5470 - 5875 MHz 2400 - 2483.5 MHz						3300 - 3600 MHz 3550 - 3800 MHz*							
CHANNEL WIDTH	5 MHz, 10 MHz or 20 MHz													
INTERFACE														
MAC (MEDIA ACCESS CONTROL) LAYER	CAMBIUM NETWORKS PROPRIETARY													
PHYSICAL LAYER	2x2 MIMO OFDM													
ETHERNET INTERFACE	10/100/1000BaseT, half/full duplex, rate auto negotiated (802.3 compliant)													
PROTOCOLS USED	IPv4, UDP, TCP, IP, ICMP, Telnet, SNMP, HTTP, FTP													
NETWORK MANAGEMENT	HTTP, Telnet, FTP, SNMP v2c													
VLAN	802.1ad (DVLAN Q-in-Q), 802.1Q with 802.1p priority, dynamic port VID													
PERFORMANCE														
ARQ	YES													
MODULATION LEVELS (ADAPTIVE)	MCS							SIGNAL TO NOISE REQUIRED (SNR, in dB)						
1X	QPSK - SISO							10						
2X	QPSK - MIMO-B							10						
4X	16QAM - MIMO-B							17						
6X	64QAM - MIMO-B							24						
8X	256QAM - MIMO-B							32						
RECEIVE SENSITIVITY (PER CHAIN, IN dB)	2.4GHz				3 GHz				5GHz					
	1X/2X	4X	6X	8X	1X/2X	4X	6X	8X	1X/2X	4X	6X	8X		
@ 5MHZ CHANNEL	-91	-86	-78	-68	-92	-86	-80	-73	-91	-85	-79	-69		
@ 10MHZ CHANNEL	-90	-83	-77	-65	-90	-83	-77	-70	-90	-83	-76	-64		
@ 20MHZ CHANNEL	-86	-80	-76	-66	-87	-80	-73	-66	-87	-80	-72	-62		
MAXIMUM DEPLOYMENT RANGE	UP TO 40 MILES													
LATENCY	3 - 5 ms, TYPICAL													
GPS SYNCHRONIZATION	YES, VIA AUTOSYNC (CMM3, CMM4, uGPS, iGPS)													
QUALITY OF SERVICE	DIFFSERVE QoS													
LINK BUDGET														
ANTENNA BEAM WIDTH	55° AZIMUTH, 55° ELEVATION (BOTH POLARIZATIONS)													
ANTENNA GAIN	9 dBi H+V, INTEGRATED PATCH (5 GHz) 8 dBi DUAL SLANT, INTEGRATED PATCH (2.4 GHz, 3 GHz)													
TRANSMIT POWER RANGE	-30 TO +22 dBm (COMBINED, TO EIRP LIMIT BY REGION) (1 dB INTERVAL) (+23 dBm FOR 3 GHz)													
MAXIMUM TRANSMIT POWER	22 dBm COMBINED OFDM (+23 dBm FOR 3 GHz)													
REFLECTOR GAIN	+14 dBi FOR 5 GHz, +12 dBi FOR 2.4 GHz AND 3 GHz													
CLIP GAIN	+8 dBi (WITH CLIP (CASSEGRAIN LENS FOR IMPROVED PERFORMANCE), FOR 5 GHz ONLY)													

PHYSICAL	
ANTENNA CONNECTION	INTEGRATED PATCH ANTENNA, CONNECTORIZED VERSIONS AVAILABLE
SURGE SUPPRESSION	IEC 61000-4-2 (ESD) 15kV (AIR), 8kV (contact) IEC 61000-4-4 (EFT) 40A (5/50ns) IEC 61000-4-5 (LIGHTNING) 100A (8/20μS)
MEAN TIME BETWEEN FAILURE	> 40 YEARS
ENVIRONMENTAL	IP55
TEMPERATURE	-40°C TO +55°C (-40°F TO +131°F), 0-95% NON-CONDESNSING
WEIGHT	0.45 kg (1 lb.)
WIND SURVIVAL	190 km/hour (118 mi/hour)
DIMENSIONS (HxWxD)	30 x 9 x 9 cm (11.75" x 3.4" x 3.4")
TYPICAL POWER CONSUMPTION	9 W (5 GHz AND 2.4 GHz), 12 W (3 GHz)
MAXIMUM POWER CONSUMPTION	12 W (5 GHz AND 2.4 GHz), 15 W (3 GHz)
INPUT VOLTAGE	20 TO 32 V
SECURITY	
ENCRYPTION	56-bit DES, FIPS-197 128-bit AES
CERTIFICATIONS	
INDUSTRY CANADA	109W-0002 (5.4, 5.8 GHz) 109W-0004 (2.4 GHz) 109W-0007 (3.5 GHz) 109W-0009 (3.65 GHz)
FCC ID	Z8H89FT0002 (5.4, 5.8 GHz) Z8H89FT0004 (2.4 GHz) Z8H89FT0009 (3.65 GHz)
CE	EN 301 893 V1.6.1 (5.4 GHz) EN 302 502 V1.2.1 (5.8 GHz) EN 302 326-2 V1.2.2 (3 GHz) EN 302 326-3 V1.3.1 (3 GHz)